



STAINLESS STEEL BODY

MAXIMUM O.A.L. 360.00"

MAXIMUM O.A.H. 112.50"

NOTE
DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.

- ONSPOT AUTOMATIC TIRE CHAINS TO BE PROVIDED AT REAR
- 10/4 BATTERY CHARGER LOCATED BEHIND DRIVER SEAT
- DUAL L.E.D. LIGHT STRIPS LOCATED IN HOSE BED
- PULL STRAP ON DOOR IN COMPARTMENTS D2 & D3
- REVERSED HINGED DOOR ON COMPARTMENTS D4 & P2
- DELETE PARTITION BETWEEN COMPARTMENTS D2 & D3
- CIRCUIT BREAKER PANEL IN COMPARTMENT D3
- HANNAY ELECTRIC REWIND BOOSTER REEL SBEP34-23-24 IN COMPARTMENT R1 WITH CAPACITY FOR 200' OF 1.00" BOOSTER HOSE WITH 1.50" PIPING
- ONE 20A, 120V RECEPTACLE IN COMPARTMENT P2
- TWO 20A, 120V SENTREX 6-PLACE RECEPTACLE STRIPS IN CAB
- ONE 20A, 120V DUPLEX RECEPTACLE IN COMPARTMENTS D3, P2 AND EACH EMS CABINET

CUSTOMER APPROVAL			
APPROVED BY:			
DATE:			
REV	DATE	BY	CH
09MAY17		NPA	DTS
18MAR17		NPA	DTS
16FEB17		NPA	DTS
29DEC16		MMF	WKL

		JOB NO.	30869
		SCALE	1:24
TITLE 2000-D-750 GAL POLY, 136" FULL HEIGHT DS, LOW PS (2) XLAYS, DELUGE, BOOSTER REEL, GENERATOR		DATE	
		FOR	RADNOR FIRE COMPANY WAYNE, PENNSYLVANIA
DWG NO. 30869AD		DRAWN BY	NPA
		CHECKED BY	CSH
ENFORCER		SHEET SIZE	D
		SHEET NO.	1 OF 1