



STAINLESS STEEL BODY MAXIMUM O.A.L. 352.00" MAXIMUM O.A.H. 113.00"

NOTE
 DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.

- BATTERY CHARGER MOUNTED BEHIND DRIVER'S SEAT
- BATTERY CHARGER INDICATOR LOCATED ON DRIVER'S SEAT RISER
- DUAL L.E.D. LIGHT STRIPS LOCATED IN HOSE BED
- TWO FIXED FULL WIDTH/DEPTH SHELVES LOCATED PER ORDER
- TWO 120V RECEPTACLES LOCATED PER ORDER
- ONSPOT AUTOMATIC TIRE CHAINS

REV	DATE	BY	CH	ENFORCER
01FEB23	BTH	COS		CHASSIS DATA
10NOV22	BTH	COS		MAKE
05OCT22	BTH	COS		PIERCE
26SEP22	BTH	COS		MODEL

Pierce MANUFACTURING INC.	JOB NO.	37611
	SCALE	1:24
TITLE 1500-D-530P, 500G WATER-30G FOAM, 129" FH LS, LOW RS (2) X-LAYS, DELUGE, BOOSTER REEL, LADDER BRACKETS	DRAWN BY	BTH
	CHECKED BY	CDU
FOR READING DEPARTMENT OF FIRE AND RESCUE SERVICES READING, PENNSYLVANIA	SHEET SIZE	D
DWG NO.	37611AD	
	SHEET NO.	1 OF 1