



- HOSEBED CAPACITIES
- ① 300' OF 1.75" - PRE-CONNECT
  - ② 300' OF 3.00" - DEAD LAY
  - ③ 1500' OF 5.00" DEAD LAY
  - ④ 200' OF 2.50" - PRE-CONNECT
  - ⑤ 300' OF 1.75" - PRE-CONNECT

ALUMINUM BODY

SIDE ROLL AND FRONTAL IMPACT PROTECTION

**NOTE**  
 DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.

- 1. SHORELINE RECEPTACLE WITH KUSSMAUL SUPER AUTO-EJECT LOCATED ON DRIVER SIDE OF THE CAB
- 2. AIR INLET WITH DISCONNECT COUPLING IN THE DRIVER SIDE STEPWELL
- 3. BATTERY CHARGER LOCATED IN COMPARTMENT PER SHOP ORDER

REV	DATE	BY	CH	ENFORCER
▽	25AUG23	KRG	-	CHASSIS DATA
▽	24JUL23	KRG	-	MAKE
▽	03JUL23	KRG	-	PIERCE
▽		KRG	-	MODEL

		PROPOSAL	900
		SCALE	DATE
TITLE	2000-D-1000P, 940G WATER, 60G FOAM, 152" PUMPER BODY LADDERS ON RS, HYD. RACK LADDER ON LS, (2) XLAYS	DRAWN BY	26JUN2023
FOR	LINGOHOCKEN FIRE COMPANY WYCOMBE, PA	CHECKED BY	N/A
DWG NO.	PRELIMINARY PRINT ONLY	SHEET SIZE	SHEET NO.
		D	1 OF 1